

SheerWeave® Style 7000 BLACKOUT FABRIC

Specifications

■ Style 7000 is uniquely designed to provide total light blockage when complete room darkening is needed. With a broad range of decorator colors and the look and feel of rich cloth, Style 7000 will enhance the beauty and function of any room.

Fire Classification: California U.S. Title 19 (small scale), NFPA 701 2004 TM#1 (small scale), BS 5867 2008 Part 2 Type B Performance, CAN/ULC S109 03 (large and small scale) and CAN/CGSB2 4.162 M80

Bacteria and Fungal Resistance: AATCC 174 1998 Part II and III

Environmental Certification: Certified to GREENGUARD and GREENGUARD Gold standards for low chemical emissions into indoor air during product usage

Lead Free: RoHS / Directive 2002/95/EC, US Consumer Product Safety Commission Section 101 and ANSI/WCMA A100.1 2007 for lead content

Acoustical Performance: NRC (Noise Reduction Coefficient) and SAA (Sound Absorption Average) tested in accordance with ASTM C423 09a

Acoustical Value: NRC .10 / SAA .08

Standard Use: Roll up shade

Warranty: 5 year interior

Standard Widths: 94" and 118" (238.8cm and 299.7cm)

Standard Roll Length: 30 Linear Yards (27.4m)

Composition: 100% Polyester with Acrylic Foamed Backing

Mesh Weight: 13.41 oz/yd² (454.67 g/m²)

Fabric Thickness: .026 in (0.66mm)

Openness Factor: Opaque

Cleaning Instructions: Fabric should be regularly dusted/vacuumed as appropriate. If commercial spot cleaners are used, they must first be tested and allowed to dry on an inconspicuous area to ensure compatibility.

airloading this fabric is not recommended.

Colors may vary slightly from swatch samples. All variations are within industry standards.



PRODUCT CERTIFIED FOR
LOW CHEMICAL EMISSIONS
UL.COM/GG
UL 2818



Solar Heat Control Properties of Phifer SheerWeave Style 7000 Fabrics Installed Internally, Zero Degree Profile Angle

Style No.	Color	* Solar Optical Properties				Shading Coefficient w/				
		TS	RS	AS	TV	Single 1/8CL	1/4CL	1/4HA	Insulating 1CL	1HA
P62	White	0	64	36	0	0.31	0.31	0.30	0.30	0.24
V40	Onyx	0	64	36	0	0.31	0.31	0.30	0.30	0.24

* Performance evaluations conducted by Matrix, Inc., Mesa, Arizona.

TS = Solar Transmittance 1/8 CL = 1/8" Clear Glass
RS = Solar Reflectance 1/4 CL = 1/4" Clear Glass
AS = Solar Absorption 1/4HA = 1/4" Heat Absorbing Glass
TV = Visual Transmittance 1 CL = 1" Insulating Clear Glass
1HA = 1" Insulating Heat Absorbing Glass

For complete technical information, current test results, performance specifications and larger samples, contact our Sun Control Marketing Dept.



P. O. BOX 1700 • TUSCALOOSA, ALABAMA 35403 1700 U.S.A.
PHONE: 205/345 2120 • TOLL FREE 1/800 221 5497
FAX: 205/391 0799 • www.phifer.com