

STYLE 7400 / 7450 SPECIFICATIONS

A picture of refined elegance, Style 7400 layers a subtle textured pattern over a soft, luxurious backing for total light blockage. Offering the face fabric of Style 7400, Style 7450 filters natural light while illuminating interior spaces. These fabrics are suitable for roller shades, Roman shades and panel track systems.

| | | | |
|--|---|--------------------------------|-----------------------------|
| STYLE 7400 FIRE CLASSIFICATION | California U.S. Title 19 (small scale) | | NFPA 701 TM#1 (small scale) |
| | IBC Section 803.1.1 (Class A Rating) | | NFPA 701 TM#2 (large scale) |
| | CAN/ULC-S 109 (large and small scale) | | CAN/CGSB2-4.162-M80 |
| STYLE 7450 FIRE CLASSIFICATION | California Technical Bulletin 117 | | NFPA 101 (Class A Rating) |
| | IBC Section 803.1.1 (Class A Rating) | | |
| Fire classifications are subject to change. Please go to phifer.com for the most current information. | | | |
| BACTERIA AND FUNGAL RESISTANCE | ASTM G21-96 | AATCC 174-1998 Part II and III | |
| | | | |
| ENVIRONMENTAL CERTIFICATION | GREENGUARD | GREENGUARD Gold | |
| | Certified to these standards for low chemical emissions into indoor air during product usage | | |
| LEAD FREE | RoHS/Directive 2002/95/EC | | |
| | ANSI/WCMA A 100.1-2007 for lead content | | |
| | US Consumer Product Safety Commission Section 101 | | |
| WARRANTY | 5-year interior | | |
| ACOUSTICAL PERFORMANCE | NRC (Noise Reduction Coefficient) and SAA (Sound Absorption Average) tested in accordance with | | |
| | ASTM C423-09a | | |
| UV PROTECTION | Style 7400 received the Seal of Approval by the Melanoma International Foundation (MIF) for effectiveness in preventing sun damage to the skin or eyes | | |
| CLEANING INSTRUCTIONS | Fabric should be regularly dusted/vacuumed as appropriate. If commercial spot cleaners are used, they must first be tested and allowed to dry on an inconspicuous area to ensure compatibility. | | |
| | Railroading this fabric is not recommended. | | |
| | Colors may vary slightly from swatch samples. All variations are within industry standards. | | |

| STYLE | 7400 | 7450 |
|------------------|--|-------------------------------------|
| WIDTHS | 118" | 118" |
| | 300 cm | 300 cm |
| ROLL LENGTH | 30 Linear Yards | 30 Linear Yards |
| | 27.4 Linear Meters | 27.4 Linear Meters |
| COMPOSITION | 100% Polyester with Acrylic Foamed Backing | 100% Polyester with Acrylic Coating |
| MESH WEIGHT | 12.53 oz/yd ² | 6.19 oz/yd ² |
| | 425 g/m ² | 210 g/m ² |
| FABRIC THICKNESS | 0.029 in | 0.0118 in |
| | 0.74 mm | 0.30 mm |
| OPENNESS FACTOR | Opaque | Light-filtering |
| ACOUSTICAL VALUE | NRC .05 / SAA .03 | NRC .25 / SAA .25 |